## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **LISTING OF CLAIMS:**

- 1. (Original) A vehicular glazing panel comprising:
  - a pane of glass,
- a first electrically conductive component which exists on a surface of the pane of glass, and
- a second electrically conductive component which is joined to the first component by a lead-free solder,

wherein the lead-free solder includes a mechanical stress modifier which inhibits the occurrence of a stress fault in the pane of glass in the region of the solder.

- 2. (Original) A glazing panel as claimed in claim 1 wherein the mechanical stress modifier comprises a metal selected from bismuth, indium or antimony.
- 3. (Currently Amended) A glazing panel as claimed in claim 1 or claim 2 wherein the lead-free solder includes tin in an amount that is less than 90 % by weight.
- 4. (Currently Amended) A glazing panel as claimed in any preceding claim  $\underline{1}$  wherein a fall in the stress ( $\sigma$ ) generated in the pane of glass, after an initial rise, is

described as a function of time (t) by:

$$\sigma = A t^n$$

wherein n is a measure of the creep rate of the lead-free solder and has a value less than -0.130.

- 5. (Currently Amended) A glazing panel as claimed in any-preceding claim 1 wherein the surface of the pane of glass is provided around its periphery with a fired-ink band, on top of which the first electrically conductive component at least partially exists.
- 6. (Original) A glazing panel as claimed in claim 5 wherein the pane of glass is toughened and the stress fault therein manifests itself as blisters in the fired-ink band and in the corresponding regions of glass.
- 7. (Original) A glazing panel as claimed in claim 5 wherein the pane of glass is one ply of a laminate and the stress fault in the pane of glass manifests itself as one or more cracks therein.
- 8. (Currently Amended) A glazing panel as claimed in any preceding claim 1. wherein the stress fault in the glazing panel manifests itself as a structural defect in the interface between the solder and the first electrically conductive component.
- 9. (Currently Amended) A glazing panel as claimed in any preceding claim 1 wherein the first and second electrically conductive components comprise a busbar

and an electrical connector respectively.

- 10. (Currently Amended) A glazing panel as claimed in any of claim 1 to 8 wherein the first and second electrically conductive components comprise an antenna element and an antenna connector respectively.
- 11. (Original) Use of lead-free solder for joining together two or more electrically conductive components that are comprised in a vehicular glazing panel, which includes a pane of glass, wherein the lead-free solder includes a mechanical stress modifier which inhibits the occurrence of a stress fault in the pane of glass in the region of the solder.
- 12. (New) A glazing panel as claimed in claim 2 wherein the lead-free solder includes tin in an amount that is less than 90 % by weight.
- 13. (New) A glazing panel as claimed in claim 12 wherein a fall in the stress ( $\sigma$ ) generated in the pane of glass, after an initial rise, is described as a function of time (t) by:

$$\sigma = A t^n$$

wherein n is a measure of the creep rate of the lead-free solder and has a value less than -0.130.

14. (New) A glazing panel as claimed in Claim 13 wherein the surface of the pane of glass is provided around its periphery with a fired-ink band, on top of which

the first electrically conductive component at least partially exists.

- 15. (New) A glazing panel as claimed in claim 14 wherein the pane of glass is toughened and the stress fault therein manifests itself as blisters in the fired-ink band and in the corresponding regions of glass.
- 16. (New) A glazing panel as claimed in claim 14 wherein the pane of glass is one ply of a laminate and the stress fault in the pane of glass manifests itself as one or more cracks therein.
- 17. (New) A glazing panel as claimed in Claim 14 wherein the stress fault in the glazing panel manifests itself as a structural defect in the interface between the solder and the first electrically conductive component.
- 18. (New) A glazing panel as claimed in claim 12 wherein the first and second electrically conductive components comprise a busbar and an electrical connector respectively.
- 19. (New) A glazing panel as claimed in claim 12 wherein the first and second electrically conductive components comprise an antenna element and an antenna connector respectively.